

品番 Fabric No.	旧品番 Previous fabric No.	組織 Type of weave	線径 Diameter	オープニング Mesh opening	開口率 Opening area	紗厚 Thickness	インク容積 Ink volume	製品巾 Available width		
								cm inch	115 45	135 53
	TNo.		μm	μm	%	μm	cm ³ /m ²			
4/10-500	10T	PW	500	2040	65	946	615			
6/15-400	15T	PW	400	1293	58	776	450			
6/15-500	15HD	PW	500	1193	50	950	475			
8/20-300	20T	PW	300	970	58	560	325			
10/25-250	25S	PW	250	766	57	484	276	●	●	●
10/25-300	25T	PW	300	716	50	560	280			
12/30-250	30T	PW	250	597	50	495	248			
14/36-100	36SS	PW	100	606	74	173	128		●	●
14/36-250	36T	PW	250	456	42	485	204			
16/40-200	40T	PW	200	435	47	377	177	●	●	●
20/50-71	50SS	PW	71	437	74	119	88	●	●	●
20/50-145	50T	PW	145	363	51	265	135			
20/50-200	50HD	PW	200	308	37	353	131			
24/60-48	60-48	PW	48	375	79	85	67		●	
24/60-54	60SS	PW	54	369	76	90	68	●	●	●
24/60-64	60-64	PW	64	359	72	106	76	●	●	●
24/60-71	60S	PW	71	352	69	116	80	●		
24/60-120	60T	PW	120	303	51	201	103	●	●	●
24/60-145	60HD	PW	145	278	43	258	111	●	●	●
27/70-48	70-48	PW	48	315	75	83	62		●	
27/70-54	70SS	PW	54	309	72	90	65	●	●	●
27/70-71	70S	PW	71	292	65	115	75	●	●	●
27/70-120	70T	PW	120	243	45	196	88			
27/70-145	70HD	PW	145	218	36	260	94			
29/74-120	74T	PW	120	223	42	201	84	●	●	●
31/80-48	80-48	PW	48	270	72	80	58		●	
31/80-54	80SS	PW	54	264	69	88	61	●	●	●
31/80-71	80S	PW	71	247	60	116	70	●	●	●
31/80-100	80T	PW	100	218	47	168	79		●	●
34/86-100	86T	PW	100	195	44	165	73	●	●	●
35/90-48	90-48	PW	48	234	69	84	58			●
35/90-54	90SS	PW	54	228	65	88	57	●	●	●
35/90-71	90S	PW	71	211	56	112	63	●		●
35/90-100	90T	PW	100	182	42	165	69		●	●
39/100-48	100SS	PW	48	206	66	80	53	●	●	●
39/100-54	100S	PW	54	200	62	87	54	●	●	●
39/100-71	100M	PW	71	183	52	111	58	●	●	●
39/100-80	100T	PW	80	174	47	132	62	●		●
43/110-71	110T	PW	71	160	48	116	56	●	●	●
43/110-80	110HD	PW	80	151	43	134	58	●	●	●
47/120-48	120S	PW	48	164	60	79	47	●	●	●
47/120-54	120M	PW	54	158	56	86	48	●	●	●
47/120-64	120-64	PW	64	148	49	103	50			●
47/120-80	120HD	PW	80	132	39	130	51			
49/125-71	125T	PW	71	132	42	125	53	●	●	●
53/135-48	135S	PW	48	140	55	78	43	●	●	●
53/135-54	135T	PW	54	134	51	85	43	●	●	●
53/135-64	135-64	PW	64	124	44	102	45			●
53/135-71	135HD	PW	71	117	39	123	48	●		●

■製品巾(生産対応状況)
 ●→通常生産品(実績に基づいて生産しておりますが、将来の供給体制を保障するものではありません。)
 空欄→受注生産品(品番によっては在庫がある場合がありますので、お気軽にお問い合わせください。)
 ■オープニング・オープニングエリア・インク容積はメッシュ数・線径に基づく計算値となっております。
 ■組織はPW=平織、TW=綾織を表しております。
 ■本規格は規格値であり、保証値ではありません。
 ■本規格は改良などのために予告なく変更する場合がありますので、予めご了承ください。

■ Available width (status of production availability)
 Circle sign=Regular product (Products are manufactured based on past records, but it does not guarantee future manufacturing conditions.)
 Blank =Ordered product (Some products may be available. Please feel free to contact us.)
 ■ Calculations of the mesh opening, opening area, and ink volume are based on the number of mesh and the diameter.
 ■ Type of weave indicates PW=plain weaving and TW=twill weaving.
 ■ The specifications are standard values and not guaranteed values.
 ■ Please note that these specifications are subject to change without prior notice for improvements.

品番 Fabric No.	旧品番 Previous fabric No.	組織 Type of weave	線径 Diameter	オープニング Mesh opening	開口率 Opening area	紗厚 Thickness	インク容積 Ink volume	製品巾 Available width		
								cm inch	115 45	135 53
	TNo.		μm	μm	%	μm	cm ³ /m ²			
59/150-48	150S	PW	48	121	51	77	39	●	●	●
59/150-54	150T	PW	54	115	46	84	39	●	●	●
59/150-64	150-64	PW	64	105	39	106	41			●
59/150-71	150HD	PW	71	98	34	111	38			
63/160-48	160S	PW	48	111	49	79	39	●	●	●
63/160-54	160T	PW	54	105	44	83	37	●	●	●
63/160-64	160-64	PW	64	95	36	102	37	●	●	●
63/160-71	160HD	PW	71	88	31	113	35			
71/180-48	180S	PW	48	93	44	74	33	●	●	●
71/180-54	180T	PW	54	87	38	83	32	●	●	●
79/200-45	200-45	PW	45	82	42	68	29			
79/200-48	200S	PW	48	79	39	73	28	●	●	●
79/200-54	200T	PW	54	73	33	82	27	●	●	●
90/225-40	225S	PW	40	73	42	59	25	●	●	●
90/225-45	225-45	PW	45	68	36	66	24			
90/225-48	225T	PW	48	65	33	72	24	●	●	●
90/225-54	225HD	PW	54	59	27	84	23	●	●	●
90/225-54	225HD	TW	54	59	27	93	25		●	
100/250-40	250T	PW	40	62	37	59	22	●	●	●
106/270-34	270T	PW	34	60	41	51	21	●	●	●
106/270-40	270HD	PW	40	54	33	59	19	●	●	●
110/280-34	280T	PW	34	57	39	51	20	●	●	●
120/300-34	300S	PW	34	51	36	51	18	●	●	●
120/300-40/34	300T	PW	40/34	49	33	57	19	●	●	●
120/300-40	300HD	PW	40	45	28	61	17	●	●	●
122/310-30	310S	PW	30	52	40	45	18	●	●	●
130/330-30	330S	PW	30	47	37	45	17	●	●	●
130/330-33	330M	PW	33	44	33	50	17			
130/330-34	330T	TW	34	43	31	60	19			
140/350-30	350S	PW	30	43	35	45	16	●	●	●
140/350-33	350M	PW	33	40	30	50	15			
140/350-34	350T	PW	34	39	29	54	16			●
140/350-34	350T	TW	34	39	29	59	17	●	●	●
150/380-30	380S	PW	30	37	30	45	14	●	●	●
150/380-33	380M	PW	33	34	26	50	13			
150/380-34	380T	PW	34	33	24	58	14			
150/380-34	380T	TW	34	33	24	60	14	●	●	●
165/420-27	420S	PW	27	33	30	40	12	●	●	●
165/420-30	420M	PW	30	30	25	45	11			
180/460-27	460S	PW	27	28	26	43	11			●

■製品巾(生産対応状況)
 ● →通常生産品(実績に基づいて生産しておりますが、将来の供給体制を保障するものではありません。)
 ○ →受注生産品(品番によっては在庫がある場合がありますので、お気軽にお問い合わせください。)
 ■オープニング・オープニングエリア・インク容積はメッシュ数・線径に基づく計算値となっております。
 ■組織はPW=平織、TW=綾織を表しております。
 ■本規格は規格値であり、保証値ではありません。
 ■本規格は改良などのために予告なく変更する場合がありますので、予めご了承ください。

■ Available width (status of production availability)
 Circle sign=Regular product (Products are manufactured based on past records, but it does not guarantee future manufacturing conditions.)
 Blank =Ordered product (Some products may be available. Please feel free to contact us.)
 ■ Calculations of the mesh opening, opening area, and ink volume are based on the number of mesh and the diameter.
 ■ Type of weave indicates PW=plain weaving and TW=twill weaving.
 ■ The specifications are standard values and not guaranteed values.
 ■ Please note that these specifications are subject to change without prior notice for improvements.