

品番 Fabric No.	組織 Type of weave	オープニング Mesh opening	開口率 Opening area	密度 Mesh count	線径 Diameter	紗厚 Thickness	製品幅 Available width		
							cm	94	122
							inch	37	48
PE 5 目	PW	4413	75	5 × 5	667	1200			
PE 8 目	PW	3083	72	7 × 7	546	930	●	●	
PE 12 目	PW	1994	62	10 × 10	546	980	●		
PE 14 目	PW	1571	55	12 × 12	546	1000	●	●	
PE 18 目	PW	1242	61	16 × 16	346	660	●	●	
PE 24 目	PW	924	53	20 × 20	346	680	●	●	
PE 30 目	PW	761	52	25 × 23	299	610	●	●	
PE 40 目	PW	527	47	34 × 32	244	500	●	●	
PE 50 目	PW	376	37	42 × 40	244	530	●	●	
PE 60 目	PW	351	45	50 × 47	173	360	●	●	
PE 70 目	PW	292	44	59 × 56	150	360	●	●	
PE 80 目	PW	276	48	67 × 61	122	250	●	●	
PE 100 目	PW	230	43	83 × 64	122	260	●	●	
PE 120 目	PW	178	35	96 × 76	122	260	●	●	
PE 150 目	PW	145	39	120 × 102	86	180	●	●	
PE 180 目	PW	129	36	144 × 100	86	190	●	●	
PE 200 目	PW	123	35	156 × 100	86	190	●	●	

■製品幅(生産対応状況)
 ● =通常生産品(実績に基づいて生産しておりますが、将来の供給体制を保障するものではありません。)
 空欄=受注生産品(品番によっては在庫がある場合がありますので、お気軽にお問い合わせください。)
 ■オープニング・オープニングエリアはメッシュ数・線径に基づく計算値となっております。
 ■組織は PW= 平織、TW= 綾織を表しております。
 ■本規格は規格値であり、保証値ではありません。
 ■本規格は改良などのために予告なく変更する場合がありますので、予めご了承ください。

■Available width (status of production availability)
 ● =Regular product (Products are manufactured based on past records, but this does not guarantee future manufacturing conditions.)
 Blank=Ordered product (Some products may be available. Please feel free to contact us.)
 ■Calculations of the mesh opening, opening area, and ink volume are based on the number of mesh and the diameter.
 ■Type of weave indicates PW=plain weaving and TW=twill weaving.
 ■The specifications are standard values and not guaranteed values.
 ■Please note that these specifications are subject to change without prior notice for improvements.